





Double Front Wheel w/Guide Wheel



FEATURES & SPECIFICATIONS:

OVERVIEW				
1.01	Model: CTR 3.0T	Unit		
1.02	Max. load capacity	kg	3000	
1.03	Max. lifting height	mm	195	
1.05	Min. height of fork	mm	80	
1.06	Load center	mm	600	
1.07	Turning radius	mm	1276	
1.08	Operation Type		Pedestrian	
1.09	Lifting Power		Manual	
1.10	Travelling Power		Manual	
1.12	Net Weight	kg	72	

2.01	Overall Length	mm	1630
2.02		mm	685
2.03	Handle Height above ground	mm	1209
2.04	Handle Length	mm	780
2.05	Fork Dimensions(L*W)	mm	1220*160
2.06	Forks Outside Width	mm	685
2.07	Forks Inside Width	e e	365
2.08	Min.ground clearance	mm	22

- Built with quality in mind.
- Practical, durable design.
- Nylon/PU wheels provide low rolling resistance.
 Makes moving loads easy.
- Powder-coated paint finish.
- One-piece cast wheel frame, equipped with double front wheels, with strong load-bearing capacity.

WHEELS & TIRES				
3.01	Wheel type		Nylon/PU	
3.02	Axle center to fork face	mm	1160	
3.03	Wheel base	mm	1260	
3.04	Wheels number drive/load		2/4pcs	
3.05	Tire size, drive	mm	Ф180*50	
3.06	Tire size,load	mm	Ф78х70	